










REV	Description	Date
A00	First Issue	2003-SEP-29



PIN ASSIGNMENT

PIN	NAME
1	V6
2	V5
3	V4
4	V3
5	V2
6	C2P
7	C2N
8	C1N
9	C1P
10	C3N
11	VEE
12	VSS
13	VDD
14	SDA
15	SCK
16	D/C
17	/RES
18	/CS1



- SPECIFICATIONS:**
- 1) FSTN/+VE/B&W/TRANSFLECTIVE MODE
 - 2) 1/65 DUTY, 1/9 BIAS, VLCD=9.0V
 - 3) VIEWING DIRECTION : 12 O'CLOCK
 - 4) OP. TEMP.= -20°C to +70°C
ST. TEMP.= -30°C to +80°C
 - 5) IC: 'SOLOMON' SSD1815, SERIAL I/O
 - 6) W/ WHITE LED BACKLIGHT, 3.6V@30mA, 50mA MAX.

Description: MECHANICAL SPECIFICATIONS

Scale: Sheet : 1 of 1

Unspecified Tol. ±0.3 Unit mm

Approvals Date **Project Number** Item Number

Draw: TMGG13264-13

Check:

Approve: Do Not Scale This Drawing

TRI-T COMPANY LIMITED

Projection